

jc530 U.S. PTO



03/01/00

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. 6801-0016

First Inventor or Application Identifier: John McEwan

Title: LOW PROFILE COMPUTER CASE AND COMPUTER

Express Mail Label No.

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO:

Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. ☒ Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original, and a duplicate for fee processing)
2. ☒ Specification Total Pages [16]
(preferred arrangement set forth below)
- Descriptive title of the Invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s) (35 USC 113) Total Sheets [6]
4. ☒ Oath or Declaration Total Pages [2]
- a. ☒ Newly executed (original or copy)
- b. ☐ Copy from a prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 17 completed)
[Note Box 5 below]
- i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation By Reference (useable if Box 4b is checked)
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered to be part of the disclosure of the accompanying application and is hereby incorporated by reference therein.

6. ☐ Microfiche Computer Program (Appendix)
7. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
- a. ☐ Computer Readable Copy
- b. ☐ Paper Copy (identical to computer copy)
- c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☒ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement ☐ Power of Attorney
(when there is an assignee)
10. ☐ English Translation Document (if applicable)
11. ☒ Information Disclosure Statement ☒ Copies of IDS
(IDS)/PTO-1449 Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
14. ☒ *Small Entity ☐ Statement filed in prior application,
Statement(s) Status still proper and desired
(PTO/SB/08-12)
15. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
16. ☐ Other:

*A new statement is required to be entitled to pay small entity fees, except where one has been filed in a prior application and is being relied upon.

17. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment
- ☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. _____
- Prior application information: Examiner: _____ Group/Art Unit: _____

18. CORRESPONDENCE ADDRESS

☒ Customer Number or Bar Code Label

Customer No 22204

or ☐ Correspondence address below

(Insert Customer No. or Attach bar code label here)

Name Marc S Kaufman
Firm NIXON PEABODY LLP
Address 8180 Greensboro Drive, Suite 800
City McLean State VA
Country U S A Telephone (703) 790-9110

Zip Code 22102
FAX (703) 883-0370

Name (Print/Type) Marc S. Kaufman

Registration No. (Attorney/Agent) 35,212

Signature

Date: March 1, 2000

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

**STATEMENT CLAIMING SMALL ENTITY STATUS
(37 CFR 1.9(f) & 1.27(c))—SMALL BUSINESS CONCERN**Docket Number (Optional)
6801-0016Applicant, Patentee, or Identifier: John A. McEwanApplication or Patent No.: New Patent Application

Filed or Issued:

Title: "LOW PROFILE COMPUTER CASE AND COMPUTER"

I hereby state that I am

- ☐ the owner of the small business concern identified below:
☒ an official of the small business concern empowered to act on behalf of the concern identified below:

NAME OF SMALL BUSINESS CONCERN Technology Advancement Group, Inc.ADDRESS OF SMALL BUSINESS CONCERN 22355 TAG WAY, Dulles VA 20166-9310

I hereby state that the above identified small business concern qualifies as a small business concern as defined in 13 CFR Part 121 for purposes of paying reduced fees to the United States Patent and Trademark Office. Questions related to size standards for a small business concern may be directed to: Small Business Administration, Size Standards Staff, 409 Third Street, SW, Washington, DC 20416.

I hereby state that the rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention described in:

- ☒ the specification filed herewith with title as listed above.
☐ the application identified above.
☐ the patent identified above.

If the rights held by the above identified small business concern are not exclusive, each individual, concern, or organization having rights in the invention must file separate statements as to their status as small entities, and no rights to the invention are held by any person, other than the inventor, who would not qualify as an independent inventor under 37 CFR 1.9(c) if that person made the invention, or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d), or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern, or organization having any rights in the invention is listed below:

- ☐ no such person, concern, or organization exists.
☒ each such person, concern, or organization is listed below.

Separate statements are required from each named person, concern or organization having rights to the invention stating their status as small entities. (37 CFR 1.27)

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

NAME OF PERSON SIGNING John A. McEwanTITLE OF PERSON IF OTHER THAN OWNER President, CEOADDRESS OF PERSON SIGNING 13809 Leighfield Street, Chantilly VA 20151-2503SIGNATURE [Signature]DATE 29 FEB 00

LOW PROFILE COMPUTER CASE AND COMPUTER

BACKGROUND OF THE INVENTION

1. Field of the Invention:

The invention relates to computer cases and computers and more specifically, the invention relates to a low profile computer case and computer.

2. Description of the Related Art:

As computers become more ubiquitous in society, it becomes more desirable to reduce the size of computer systems. Currently, there is a clear trend toward more powerful and more compact computer systems. Accordingly, the consumed power per unit density, i.e. the power density, of the average computer has increased tremendously over the past several years. However, such an increase in power density runs into a limitation of heat dissipation. More specifically, the higher the power density, the more heat generated and the more difficult it is to dissipate the heat. Of course, heat adversely affects the operation of most microprocessor based components and other computer components. Accordingly, the desire to reduce the size and increase the power of computers is at odds with the need to maintain components at temperatures within desired operating ranges.

Essentially, there are two processes by which heat in a computer case is dissipated. The first process is "air exchange cooling" which consists of replacing heated air in the case with cooler air, e.g. ambient air. The second process is "forced cooling" in which air is moved across the surface of a specific component to raise the convective heat transfer coefficient for the surface of the component thereby cooling the component faster than if the component was in static air. Most computer cases incorporate both heat dissipation processes to some degree. Both processes require the

movement of air.

It is well known to use fans to move air through computer cases to cool various components therein. Conventionally, such fans are placed in a front panel or a back panel of the computer case. However, the desire to reduce the size of computers requires that front and back panel space be utilized efficiently for accessible components such as communication ports and power connections on the back panel, and removable media and fixed media drives on the front panel. Accordingly, the use of a fan in the front or back panel wastes precious panel space. Fans have been placed in side panels to avoid this problem. However, popular rack mount systems, such as systems complying with Engineering Industries Association Standard 310-C (EIA-310-C), require that the computer case be mountable in a rack having sides that closely oppose side panels of the computer case. Accordingly, side panels of the racks may interfere with operation of fans mounted in side panels of computer cases and thus the practice of mounting fans in side panels of computer cases has limited application. Further, it is often desirable to mount sliding rails on the computer case to permit it to be slid out of the rack for maintenance and the like. Such rails interfere with fans mounted in side panels. The use of shelves to avoid the need for rails restricts vertical room.

It is also known to provide one or more fans in an interior of a computer case. U.S. patent 5,793,610 is exemplary of references disclosing such an arrangement. U.S. patent 5,793, 610 discloses a computer case having a support member in an interior of the case. Plural cooling fans are mounted in the support member. If one of the fans fails, air tends to re-circulate back through the opening in which the failed fan is mounted and thus a complex louver arrangement is provided.

U.S. patent 5,168,424 discloses a data storage unit having a housing and internal plate 105. Two open loop dc centrifugal fans are mounted in plate 105 to draw air from an area housing memory devices to an area housing a power supply. U.S. patent 5,168,424 uses dual entry open loop

centrifugal fans to adjust for a variable impedance to air flow caused by varying numbers of memory devices on the upstream side of the fans. The downstream side of the fans contains only a power supply over which air flows to vents in a front panel and thus does not present significant impedance to the system. The intake ports of the fans are positioned opposite data storage devices. The use of two centrifugal fans having intake ports opposite devices requires a large amount of space in the chassis and thus the arrangement disclosed in U.S. patent 5,168,424 is not suitable for a low profile computer chassis which includes a motherboard and other components that require additional space in the chassis.

EIA-310-C, the disclosure of which is incorporated herein by reference, specifies three different rack sizes and the sizes and tolerances of cases that can be disposed in the racks in an attempt to insure that computers and components from various vendors will fit in the same racks. There are three standard panel widths, i.e. rack sizes, 19", 24", and 30", with 19" being the most common. The vertical or height dimension of the racks is divided into a plurality of individual units known as a "U". In particular, one U equals 44.45mm \pm 0.4mm. The horizontal or width dimension of a case for a 19" rack is 482.6mm \pm 0.4mm. Many computer servers or the like are housed in a 6U case, i.e. a case that fits in the width dimension of the 19" rack noted above and is 266.7mm high (44.45mm x 6 = 266.7mm - 0.8mm tolerance to permit sliding the case into and out of the rack as prescribed by EIA-310-C).

In accordance with the recent trend in miniaturization, servers have been reduced to 2U cases, i.e. cases 88.1mm in height. However, conventional 2U servers have at most four media drives in the front panel because of the need for fans and to allow for adequate air flow for forced cooling. While components, such as media drives have gotten smaller, at any given time they are designed to fit into standard form factors, such as "half height" drives (approximately 1 5/8 " in height) and "low profile" drives (approximately 1" in height). Accordingly, case size and cooling

considerations have limited the number of components, such as various media drives, that can be housed in a 2U case. Accordingly, the functionality and flexibility of conventional computers and computer components in 2U cases is limited.

5 It is important to utilize the limited width of EIA-320-C to its fullest extent also. Accordingly, conventional cases made to fit into standard EIA-310-C racks have side walls with a lip that extends across the top of the case to a small degree to allow a top panel to be screwed onto the lip from the top of the case thereby maximizing the width of the case. As noted above, many
10 cases designed for rack mounting have slide out rails, i.e. drawer slides with rollers, that permit the case to be easily slid out of the rack and maintained in position for repair, maintenance and troubleshooting. The case including the slide out rails must fit within the standard rack width. Therefore, the use of rails, further limits the effective width of a case. Finally, an increased number
15 of components results in an increased number of communication and power cables. If the cables are too bulky and not managed properly, they further restrict air flow and thus cooling. Cabling is one more consideration that puts increased component density at odds with cooling requirements.

SUMMARY OF THE INVENTION

20 It is an object of the invention to overcome the density/cooling limits of conventional standard rack mount computer cases.

 It is another object of the invention to maximize the component space in a standard sized computer case.

25 It is another object of the invention to maximize the volume of airflow in a computer case.

 It is another object of the invention to minimize the footprint of a cooling device in a computer case.

 It is another object of the invention to use standard "off-the-shelf" components in a compact case.

A first aspect of the invention is a computer case of a standard height adapted to be mounted in a rack of a standard width, and configured to house plural computer components. The computer case comprises an enclosure defined by a front panel, a back panel, two side panels, a top panel, and a bottom panel. A partition is disposed in the enclosure and extends substantially from the bottom panel to the top panel to divide the enclosure into at least a first zone adapted to receive a mother board and a second zone adapted to receive at least one storage device. A centrifugal blower is coupled to an aperture in the partition to cause air flow between the first zone and the second zone.

A second aspect of the invention is a computer case of a standard height adapted to be mounted in a rack of a standard width, and configured to house plural computer components. The computer case comprises an enclosure defined by a front panel, a back panel, two side panels, a top panel, and a bottom panel. A partition is disposed in the enclosure and extends substantially from the bottom panel to the top panel to divide the enclosure into at least a first zone and a second zone. A first centrifugal blower is coupled to an aperture formed in the partition to cause air flow between the first zone and the second zone. An Inlet of the first centrifugal blower faces towards the top panel. A second centrifugal blower is also coupled to the aperture to cause air flow between the first zone and the second zone. An inlet of the second centrifugal blower faces towards the bottom panel and a top surface of the second centrifugal blower opposes a bottom surface of the first centrifugal blower.

BRIEF DESCRIPTION OF THE DRAWING

The invention will be described through a preferred embodiment and the attached drawing in which:

Fig. 1 is a top view of a computer in accordance with the preferred embodiment with a top panel of the case removed;

Fig. 2 is a sectional view taken along line 2-2 of Fig. 1;

Fig. 3 is a sectional view taken along line 3-3 of Fig. 1 with some components removed for clarity;

Fig. 4 is a partial sectional view taken along line 4-4 in Fig. 1;

5 Fig. 5 is a front view of the front panel of the computer of Fig. 1; and

Fig. 6 illustrates a modified partition in accordance with the preferred embodiments.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

10 Figs. 1-5 illustrate a preferred embodiment of the invention. Computer 10 includes case 20 component bays 30, 32, and 34, mother board 36, and power supply 38. Case 20 of the preferred embodiment is a standard 19" rack mount, 24" deep, 2U case. In other words, case 20 defines a rectangular enclosure that is dimensioned to fit into a standard EIA-310-C 2U space in a 19" rack. As illustrated in Figs. 1 and 2, case 20 is constructed of 15 front panel 22, side panels 24, back panel 26 bottom panel 27, and top panel 28. Note that, as illustrated in Figs. 2 and 3, side panels 24 and bottom panel 27 can be formed of a single sheet with side panels 24 defined by right angle bends in the sheet. Partition 40 extends laterally between side panels 24 and vertically from bottom panel 27 to top panel 28 to divide case 20 into 20 two zones. Aperture 42 is formed in partition 40. Blowers 44 and 48 are mounted in case 20 in the manner described below. Blowers 44 and 48 are centrifugal blowers, such as standard 96mm blowers having mounting channels 53 (blower 48) and mounting channels 55 (blower 44) respectively. For example blowers 44 and 48 can each be a GAMMA 30™ blower sold by 25 Nidec under the part number A34124-33. Manufactures of similar blowers having the same form factor include Delta, Adda, and Indec.

As illustrated in Fig. 2, aperture 42 comprises two rectangular portions 42a and 42b that abut one another. Each rectangular portion is sized to snugly receive an outlet port of one of blowers 44 and 48. In particular, outlet

port 45 of blower 44 is disposed in rectangular portion 42a of aperture 42 and outlet port 49 (see Figs. 2 and 3) of blower 48 is received in rectangular portion 42b of aperture 42. Accordingly, operation of blowers 44 and 48 creates a low pressure in a zone in front of partition 40 and a high pressure in a zone behind partition 40. Of course, this pressure differential results in air flow between the two zones through blowers 44 and 48. In particular, air flows in grills formed in front panel 22, and/or front panels of devices, into inlet 43 of blower 44 and inlet 47 (see Fig. 3) of blower 48, out of outlet ports 45 and 49 of blowers 44 and 48 respectively, and out of holes formed in back panel 26.

Fig. 3 illustrates the mounting configuration of blowers 44 and 48 in detail. Standoffs 57, such as PEMs™, are fixed to a surface of bottom panel 27 and blower 48 is disposed over standoffs 57. Specifically, one of mounting channels 53 of blower 48 abuts the top of one of spacers 57 and one of mounting channels 55 of blower 44 is aligned with the other of spacers 57. Bolts 54 are passed through mounting channels 53 and 55 and tubular spacers 59 and threaded into a tapped hole formed in respective standoffs 57. Tightening bolts 54 serves to fix blowers 44 and 48 in place with inlet 43 of blower 44 facing towards top panel 28 and inlet 47 of blower 48 facing towards bottom panel 27. Note that aperture 42 receives outlet ports 45 and 49 snugly to further support blowers 44 and 48.

Standoffs 57 are sized to provide a standoff distance x between bottom panel 27 and blower 48. Distance x defines an intake area that is roughly distance x multiplied by the circumference of inlet 47 of blower 48. The intake area preferably is substantially equal to or greater than the area of Inlet 47 (which is similar to inlet 43) of blower 48. Accordingly, blower 48 is not choked or hindered in performance in any way even though inlet 47 faces bottom panel 27. Similarly, a standoff distance of y is defined between top panel 28 and blower 44. Distance y defines an intake area that is roughly distance y multiplied by the circumference of inlet 43 of blower 44. This

intake area preferably is substantially equal to or greater than the area of inlet 43 of blower 44 to avoid hindering the performance of blower 44.

In the preferred embodiment, case 20 is a 2U case and thus has an outer height dimension of 88.1mm or roughly 3.47" at maximum. Assuming that top panel 28 and bottom panel 27 are each 90 mil (i.e. .090") thick, the inner height of case 20 between top panel 28 and bottom panel 27 is 3.29". Typical 96mm blowers are 33mm (1.3") thick. Therefore, two such blowers stacked on one another as illustrated take up at least 2.6" in the height dimension. Therefore, dimensions x and y can each be equal to about .345", ((3.29-2.6)/2=.345). Applicant has found that x and y can be preferably in the range of .206"-.370" inches inclusive, and most preferably in the range of .250" to .345", inclusive. Of course it is preferable to reduce the height of case 20 slightly below the maximum 2U specification to allow for torsion, and other variations. Therefore, x and y may be equal to about .250". Of course, when one of x and y is larger, the other becomes smaller.

The blower arrangement of the preferred embodiment permits two standard 96mm blowers to be positioned in a 2U case while only presenting the footprint of one 96mm blower. In other words the back to back stacked arrangement of blowers 44 and 48 minimizes their affective footprint by overlapping the footprints of blowers 44 and 48. Also, bays 30 and 34 are designed to accept components such as two standard width half height removable hard drives or three standard low profile hard drives. Half height hard drives have a length of roughly 6", a width of roughly 4", and a height of about 1 5/8". Therefore, three such drives can be stacked one on another in bays 30 and 34 within the dimensions of a 2U case because there is no need to place fans in front panel 22.

As illustrated in Figs. 1 and 5, bay 32 can accept DAT (digital audio tape) drive 112 that typically is about 1 5/8" high and PC card chassis 114 that typically is about 1" high. Bays 30 and 34 can each contain two ruggedized removable half height hard drives. In particular hard drives 100

and 102 are disposed in bay 30 and hard drives 104 and 106 are disposed in bay 34. The depth of standard half height hard drives is accommodated by bays 30 and 34 as illustrated in Fig. 1. Bay 30 can also accommodate pilot lights or buttons 120 and low profile floppy drive 110. Further low profile CD ROM drive 116 can also be housed in bay 34. As illustrated in Fig. 1, this configuration leaves a void space in the zone between partition 40 and bay 32. Blowers 44 and 48 in the configuration described above fit into this void space while permitting adequate air flow around bays 30, 32, and 34. Also, because inlet 45 and 49 face upward and downward respectively, cables (such as ribbon cable 60) and other conductors can be directed around side portions of blowers 44 and 48 as illustrated in Fig. 1. Such cables can provide communications and power connections between the various components. Also, typical 96mm blowers deliver about 25 ft³/min of airflow. Accordingly, the preferred embodiment has 50 ft³/min of airflow therethrough. Should one of blowers 44 and 48 fail, the other blower can adequately cool the various components for limited duty. A standard tachometer feedback can be used to detect failure of a blower and to enunciation of an alarm or the like.

Motherboard 36 includes plural memory module slots 50 (for supporting SDRAM memory modules, EDO memory modules, SIMMS memory modules, DIMMS memory modules, or the like), expansion card slots 52 (PCI, ISA, EISA, AGP, or the like), processor 54 and various other components and connectors in a known manner. The well known "ATX form factor" motherboard is roughly 12" x 13". Power supply 38 can be a standard 2U power supply. The dimensions of standard power supplies are about 4.5" X 8.25". Accordingly, power supply 38 and motherboard 36 can be placed next to one another as shown within the width dimension of case 20 which is made to fit in a standard 19" rack.

As illustrated in Figs. 1-3, partition 40 has bent portions formed on an upper edge thereof to define cable channels 41 extending through partition 40

to permit power cables, communication cables, and the like to pass through partition 40. For example, ribbon cable 60 from an IDE hard drive in bay 34 extends through either one of channels 41 to an IDE controller connector on motherboard 36. As illustrated in Fig. 4, each channel 41 is defined by

5 bending a portion of the top edge of partition 40 at roughly a 90 degree angle.

Of course, it may be necessary to form small cuts in partition 40 to define the width of channel 41. The width of channel 41 can be set to be slightly larger than the width of the largest ribbon cable to extend therethrough. It can be seen that the bent portion defines a smooth flat surface of channel 41 on
10 which ribbon cable 60 can rest. Also, resilient member 62 (illustrated with a dotted line for clarity), such as a gasket or other seal, can be disposed on a surface of top panel 28 in opposition to the top edge of partition 40 to seal channel 41 around ribbon cable 60. Resilient member 62 can extend along the entire length of partition 40 or only in opposition to channels 41 or other
15 portions of partition 40.

As illustrated in Fig. 2, top panel 28 includes wrap-around portions 29 that extend substantially orthogonally to main portions of top panel 28. Wrap-around portions 29 permit top panel 28 to be secured to side panels 24 by fasteners, such as screws 66, which extend through wrap-around portions 29
20 and side panels 24. This arrangement avoids screw heads on the main portion of top panel 28 to thereby reduce the clearance needed between top panel 28 and another unit disposed in a rack directly above top panel 28. Accordingly, case 20 can have a slightly larger inner height dimension or top panel 28 can be slightly thicker to increase the mechanical strength and
25 rigidity of case 20. Further, wrap-around portions 29 extend into a void space defined by slide out mounting rails 70 which are attached to side panels 22. Accordingly, wrap-around portions 29 do not add to the effective width dimension of case 20 which must fit into a standard sized rack. Fig. 2 illustrates slide out rails 70 on case 20. It can be seen that any portion of the
30 heads of screws 66 that extends beyond wrap-around portions 29 will extend

into a void space defined by rails 70 between side panels 24 and sides of rack 72 (shown with a dotted line) in which case 20 is mounted.

Fig. 6 illustrates case 10 having modified partition 40 having offset portions 40a and 40b connected by connecting portion 40c. This arrangement allows different proportions of the zones for accommodating a mini ATX motherboard in a shallower case for example. Other elements for the case of Fig. 6 are similar to that of Fig. 1 and are unillustrated or labeled with like reference numerals.

The invention can have any components in any configuration. For example, various power supplies, drives, motherboards switches and memory devices can be used. The invention can be used in any size computer. The case can be rack mounted or free standing.

While the foregoing description includes many details and specificities, it is to be understood that these have been included for purposes of explanation only, and are not to be interpreted as limitations of the present invention. Many modifications to the embodiments described above can be made without departing from the spirit and scope of the invention, as is intended to be encompassed by the following claims and their legal equivalents.

What is claimed is:

1. A computer case of a standard height adapted to be mounted in a rack of a standard width, and configured to house plural computer components, said computer case comprising:

5 an enclosure defined by a front panel, a back panel, two side panels, a top panel, and a bottom panel;

a partition disposed in said enclosure and extending substantially from said bottom panel to said top panel to divide said enclosure into at least a first zone adapted to receive a motherboard and a second zone adapted to receive at least one memory device, an aperture being formed in said partition; and

a centrifugal blower coupled to said aperture to cause air flow between said first zone and said second zone.

15 2. A computer case as recited in claim 1 wherein an outlet of said centrifugal blower is disposed in said aperture.

20 3. A computer case as recited in claim 1, comprising two centrifugal blowers, an outlet of each of said blowers being disposed in said aperture.

4. A computer case as recited in claim 3, wherein said two centrifugal blowers comprise a first centrifugal blower having an inlet facing said bottom panel and a second centrifugal blower having an inlet facing said top panel.

25 5. A computer case as recited in claim 4, wherein a first standoff dimension is defined between said inlet of said first centrifugal blower and said bottom panel, said first standoff dimension multiplied by the perimeter of the inlet said first centrifugal blower defining an area that is substantially equal to or greater than an inlet area of said first centrifugal blower.

6. A computer case as recited in claim 5, wherein a second standoff dimension is defined between said inlet of said centrifugal second blower and said top panel, said second standoff dimension multiplied by the perimeter of said inlet of said second centrifugal blower defining an area that is substantially equal to or greater than an inlet area of said second centrifugal blower.

7. A computer case as recited in claim 6, wherein each of said side panels have sliding rails mounted on an outside surface thereof, and wherein said top panel comprises two wrap-around portions that extend over top portions of a respective one of said side panels, said wrap-around portions each extending into a respective void space defined by said sliding rails between said side panels and an outer dimension of said sliding rails.

8. A computer case as recited in claim 6, further comprising at least one bent portion formed in an edge of said partition to define a surface on said partition that is offset from the edge of said partition, a wire channel being defined on said surface.

9. A computer case as recited in claim 6, wherein said first centrifugal blower and said second centrifugal blower are standard 96mm blowers.

10. A computer case as recited in claim 6, wherein said first centrifugal blower and said second centrifugal blower create a positive pressure in said first zone and a negative pressure in said second zone.

11. A computer case as recited in claim 6 wherein said first standoff dimension and said second standoff dimension are each in the range of .200-.370 inches, inclusive.

12. A computer case as recited in claim 6 wherein said first standoff dimension and said second standoff dimension are each in the range of .250-.345 inches, inclusive.

5 13. A computer case as recited in claim 4 further comprising three bays defined in said second zone and configured to hold components requiring access through said front panel, two of said bays extending substantially from said front panel to said partition, the other of said bays extending from said front panel toward said partition to a lesser degree to
10 define a void space between said partition and said other of said bays, said first centrifugal blower and said second centrifugal blower being disposed in said void space.

15 14. A computer case of a standard height adapted to be mounted in a rack of a standard width, and configured to house plural computer components, said computer case comprising:

 an enclosure defined by a front panel, a back panel, two side panels, a top panel, and a bottom panel;

20 a partition disposed in said enclosure and extending substantially from said bottom panel to said top panel to divide said enclosure into at least a first zone and a second zone, an aperture being formed in said partition;

 a first centrifugal blower coupled to said aperture to cause air flow between said first zone and said second zone, an inlet of said first centrifugal blower facing towards said bottom panel;

25 a second centrifugal blower coupled to said aperture to cause air flow between said first zone and said second zone, an inlet of said second centrifugal blower facing towards said top panel, a top surface of said second centrifugal blower opposing a bottom surface of said first centrifugal blower.

30 15. A computer case as recited in claim 14, wherein a first standoff

dimension is defined between said intake port of said first centrifugal blower and said bottom panel, said first standoff dimension multiplied by the perimeter of said inlet of said first centrifugal blower defining an area that is substantially equal to or greater than an inlet area of said first centrifugal blower.

16. A computer case as recited in claim 15, wherein a second standoff dimension is defined between said intake port of said second centrifugal blower and said top panel, said second standoff dimension multiplied by the perimeter of said second centrifugal blower defining an area that is substantially equal to or greater than an inlet area of said second centrifugal blower.

17. A computer case as recited in claim 14 wherein said first standoff dimension and said second standoff dimension are each in the range of .200-.370 inches, inclusive.

18. A computer case as recited in claim 14 wherein said first standoff dimension and said second standoff dimension are each in the range of .250-.345 inches, inclusive.


19. A computer case as recited in claim 1, wherein said partition comprises two offset portions and a connecting portion extending between the offset portions, said aperture being formed in said connecting portion.

LOW PROFILE COMPUTER CASE AND COMPUTER

ABSTRACT

A low profile computer case having two centrifugal blowers mounted in a partition therein. An intake port of a first blower faces a bottom panel of the case and an intake port of the second blower faces a top panel of the case.

- 5 Standoff dimensions are defined between the respective intake ports and panels to permit operation of the blowers.






Fig. 2




Fig. 3




Fig. 4

FIG. 4





Fig. 5



6. 1. 1.

DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

Attorney Docket No. 6801-0026

As a below named inventor, I hereby declare that: my residence, post office address and citizenship are as stated next to my name; that I verily believe that I am the original, first and sole inventor (if only one name is listed below) or a joint inventor (if plural inventors are named below) of the invention entitled: LOW PROFILE COMPUTER CASE AND COMPUTER

_____, the specification of which is attached hereto unless the following box is checked:

☐ The specification was filed on _____
and was assigned Serial No. _____
(if known)
and was amended on _____
(if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56.

I do not know and do not believe the same was ever known or used in the United States of America before my or our invention thereof, or patented or described in any printed publication in any country before my or our invention thereof, or more than one year prior to this application, that the same was not in public use or on sale in the United States of America more than one year prior to this application, that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this application in any country foreign to the United States of America on an application filed by me or my legal representatives or assigns more than twelve months prior to this application, and that no application for patent or inventor's certificate on this invention has been filed in any country foreign to the United States of America prior to this application by me or my legal representatives or assigns, except as follows:

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and checked at right:

Prior Foreign Application(s)			Priority Claimed	
(Number)	(Country)	(Month/Day/Year Filed)	Yes	No

All foreign applications, if any, for any Patent or Inventor's Certificate filed more than 12 months prior to the filing date of this application:

Country	Application No.	Date of Filing (Month/Day/Year)

I hereby claim the benefit under Title 35, United States Code, §119(e) or §120, as applicable, of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

Application Serial No.	Filing Date	Status: patented, pending, abandoned

I hereby appoint the following attorneys to prosecute this application and/or any international application and to transact all business in the Patent and Trademark Office connected therewith:


Daniel W. Sixbey, (Reg. No. 20,932)	Stuart J. Friedman (Reg. No. 24,312)
Charles M. Leedom, Jr. (Reg. No. 26,477)	Gerald J. Ferguson, Jr. (Reg. No. 23,016)
David S. Safran (Reg. No. 27,997)	Thomas W. Cole (Reg. No. 28,290)
Joan K. Lawrence (Reg. No. 29,940)	Donald R. Studebaker (Reg. No. 32,815)
Jeffrey L. Costellia (Reg. No. 35,483)	Tim L. Brackett (Reg. No. 36,092)
Eric J. Robinson (Reg. No. 38,285)	Robert M. Schulman (Reg. No. 31,196)
Thomas M. Blasey (Reg. No. 33,475)	Daniel S. Song (Reg. No. 43,143)
Marc S. Kaufman (Reg. No. 35,212)	Corinne R. Gorski (Reg. No. 34,339)
William J. Healey (Reg. No. 36,160)	Robin C. Clark (Reg. No. 40,956)

Send Correspondence to:

NIXON PEABODY LLP
8180 Greensboro Drive, Suite 800
McLean, Virginia 22102
Telephone: (703) 790-9110

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

The undersigned hereby authorize any U.S. attorney or agent named herein to accept and follow instructions from _____ as to any action to be taken in the Patent and Trademark Office regarding this application without direct communication between the U.S. attorney or agent and the undersigned. In the event of a change in the persons from whom instructions may be taken, the U.S. attorneys or agents named herein will be so notified by the undersigned.

FULL NAME OF SOLE OR FIRST INVENTOR John A. McEwan	INVENTOR'S SIGNATURE 	DATE 29 FEB 00
RESIDENCE (City, State & Country) 13800 Leighfield Street, Chantilly, VA 20151-2503		CITIZENSHIP United States of America
POST OFFICE ADDRESS (Complete Address including City, State & Country)		